



Planet Scuba India

Ocean Technology Systems Product Catalog

Sport - Search & Rescue - Commercial - Military
Scientific - Film / TV - Government



Innovative Solutions for Underwater Communications

Undersea Systems International, Inc.

DBA

OCEAN TECHNOLOGY SYSTEMS

3133 W. Harvard St. • Santa Ana, California 92704 • Telephone: 714/754-7848 • FAX 714/966-1639

July 3, 2019

To Whom It May Concern,

CERTIFICATE

Representation of Undersea Systems International, Inc., doing business as Ocean Technology Systems having its principal office as 3133 W. Harvard Street, Santa Ana, California, 92704, USA.

We hereby confirm that the below mentioned company,

Planet Scuba LLP.
1315 Double Road
2nd Stage, Indiranagar
Bangalore 560038
India

Is one of our (Official) distributors for the Guardian Full Face Masks, Aquacom, Buddy Phone, Buddy Line and our full line of through-water and hard wire products. They are authorized to sell in India.
This appointment is valid for one year from the date of this letter and can be cancelled by either party with a 30-day notice.

Sincerely,



Dennis Sakamoto
International Sales Representative
Ocean Technology Systems





Table of Contents

Full Face Masks : Guardian and Spectrum	8 - 11
Full Face Mask Accessories	14 - 15
Wireless Communications	18 - 21
Wireless Communications Specifications	22- 23
Hardwire Communications	26 - 29
Hardwire Communications Specifications	29
Military Communications	32 - 33
Military Communications Specifications	34 - 35
Diver Recall Systems	38
Diver Recall Systems Specifications	39
Audio Recording	42 - 43



Ocean Technology Systems

THE AMERICAN DREAM

In 1984, Mike Pelissier and Jerry Peck had a dream—design the best underwater communications on the market. With drive and determination, the two men started building what was to become a worldwide brand from their garage. With Jerry's engineering design background and Mike's Navy Diver and sales experience, the two partners were a dynamic duo. As the company grew Mike and Jerry's goal was to always take care of the customer providing the highest quality products at a fair price.

OTS is now the leader and trusted choice for underwater communications in the industry. Militaries, professional dive teams, recreational divers, scientific divers, government agencies as well as Film & T.V. productions around the world have made OTS their go to for their underwater communication needs.

With over 30 years as experts in underwater communications, OTS has continued to grow and thrive creating new products and fulfilling the needs of market demands. The OTS product line covers underwater communications for all applications as well as full face masks. Today OTS continues to be family owned and operated and the mission remains the same, to provide innovative solutions for underwater communications and serving their customers worldwide.

"We invite you to join the ranks of many elite and satisfied customers in the US and abroad who allow us to serve them."

Michael Pelissier & Jerry Peck

- Owners





IT'S TIME FOR AN **UPGRADE**

OTS Full Face Masks' (FFM) are second to none in comfort, style, fit, and function. We offer the best FFM in field of vision and have designed our masks with the most user friendly features. Whether you are a working diver looking to use a FFM for practical application or a sport diver looking to take your diving experience to the next level, we are confident we have the FFM for you!



THE GUARDIAN

FULL FACE MASK

With the Guardian Full Face Mask (GFFM) we designed a Full Face Mask (FFM) that we felt encompassed what was missing with other FFMs on the market. We wanted to create a product durable and rugged with all inclusive features such as a built in Ambient Breathing Valve® (ABV) to conserve tank air, an easily removable second stage regulator, superb field of vision and a self-defogging system.

We also wanted to ensure that fit and function were at the forefront of the design. The Guardian FFM eliminates the need for a bite down regulator which curbs dry mouth and eliminates jaw fatigue.

Our comfortable no leak double seal allows for more faces to fit our standard design than any other mask on the market. Our easily removable straps allow for more forgiving usage lessening the risk of tearing the skirt. The Guardian FFM side mounted regulator adds to the masks low profile and automatically keeps bubbles out of your view. Throw in a customizable equalizing block to allow for easy clearing of your ears and we have all your bases covered.

The GFFM is the premier choice for any diver looking for durability, luxury, and an easy to use product.

MULTIPLE COLOR OPTIONS AVAILABLE!




Black/Black



Black/Blue



Blue/Black



Black/Pink



Yellow/Black




Black/Red

FEATURES



REMOVABLE 2ND STAGE REGULATOR

Our one touch regulator quick release allows easy removal of the 2nd stage regulator for a no fuss user experience and streamlined gear maintenance



DOUBLE FACE SEAL

Our soft yet durable no leak double seal allows for a one size design fitting more faces than any other mask on the market.



AMBIENT BREATHING VALVE (ABV®)

The ABV® allows the user to conserve tank air while at the surface by simply rotating the ABV open.



QUICK DISCONNECT ASSEMBLY

The internal quick disconnect assembly allows a user to quickly detach their regulator from the mask, eliminating the need for a hose QD.



5 POINT HEAD HARNESS

A 5 point head harness ensures the diver has a secure fit of the mask to their face and eliminates the likelihood of the mask unintentionally coming off.



SELF-DEFOGGING AIRFLOW SYSTEM

Our self defogging airflow system ensures the Guardian FFM stays fog free throughout your entire dive, every time.



BUILT FOR EVERYONE

With the design challenge in mind to cover a wider “spectrum” of divers, we wanted to create a Full Face Mask (FFM) that put the price control in the hands of the user without sacrificing design, look, or function. The Spectrum Full Face Mask (FFM) serves as the most customizable FFM with the best price on the market allowing you to decide which features you’ll pay for.



SPECTRUM FULL FACE MASK

The Spectrum FFM's soft flexible material feels like a dream in comfort. Its lightweight design makes traveling with a FFM easier and more cost effective than ever before. Unlike most other FFMs, The Spectrum offers a pinch-your-nose method ensuring that those new to FFM diving have a familiar experience. The Spectrum FFM also allows you to use most any second stage regulator ensuring you don't have to give up your favorite regulator while diving FFM.

With add on options such as the Ambient Breathing Valve® (ABV) to conserve air at the surface, mounts/ brackets for adding cameras or lights, and communications to stay connected, you now have the option to build your mask how you want it or stick with the bare necessities.

USE YOUR OWN REG

Don't be forced to give up your favorite regulator while using a Full Face Mask (FFM). The Spectrum FFM allows you to use virtually any modern standard second stage regulators with easy installation and removal.



EASY EQUALIZATION

Equalizing is a breeze with The Spectrum FFM's pinch-your-nose method. There are no assemblies or adjustments to make. Just pinch-your-nose and go!

COMMUNICATIONS COMPATIBILITY

Use any of our easy to install wireless or hardwire communications with our Spectrum FFM to stay connected while you dive.

*Guardian communications are interchangeable.



MULTIPLE COLORS AVAILABLE!

- Black Skirt / Coated Lens
- Black Skirt / Clear Lens
- Blue Skirt / Coated Lens
- Blue Skirt / Clear Lens





ACCESSORIES

Our extensive collection of accessories are great additions to your Full Face Mask whether you are using the tough Guardian Full Face Mask or the innovative Spectrum Full Face Mask. Need extra light while diving at night or want to capture your dive by adding a camera to your mask? How about both? We got you covered.



GFFM RAIL SYSTEM

with SOLA 800 / 1200

The GFFM Accessory Rail System easily attaches to the Guardian Full Face Mask and makes it possible to mount various devices to the sides of the mask including a SOLA 800/1200 light. The quick disconnect feature allows surface support to quickly exchange or replace devices as the mission dictates without removing the mask from the diver, or the diver from the water. Can be mounted on either side of the mask.



GFFM RAIL SYSTEM

with Universal Light Bracket

The Accessory Rail System with Universal Light Bracket allows virtually any light to be mounted to the Guardian Full Face Mask. One rail may be used or two may be mounted (one on each side). The attachment method does not interfere with ABV® (Ambient Breathing Valve).

GOPRO® / LIGHT COMBO MOUNT

Compatible with GFFM Rail System / Spectrum Bracket

Adding this Inodive mount to a Rail System Slide allows you to mount a GoPro® camera and a light on the same slide. This will work with Universal Slide, Inodive Light, as well as Light & Motion SOLA Lights (Requires SOLA Mount Slide & D Ring it).



SPECTRUM ABV®

The OTS Spectrum Ambient Breathing Valve allows a diver to conserve tank air by simply opening the valve on the mask! This is a great addition for any diver who waits for their dive buddy to finish getting ready or hanging out on the surface after a dive!

SPECTRUM CAMERA MOUNT

The OTS Spectrum Camera mount allows for quickly mounting a GoPro® or similar type camera! It is easily attached to the top frame of the mask via a single screw allowing a diver to record video hands free during a dive!



SPECTRUM UNIVERSAL LIGHT BRACKET

The Spectrum Accessory Bracket allows a diver to mount most (round) 3rd party lights to the side of the Spectrum Full Face Mask. This is great for night dives or anytime where additional light is required! The Spectrum Accessory Bracket allows for two mounting positions : high or low.



GUARDIAN FFM EYEWEAR KIT

Add your prescription lenses to wire frames in your OTS Guardian FFM. Enjoy a clear view underwater with securely mounted, custom engineered and field tested prescription ready eye gear.

360° SWIVELS / 90° ELBOWS & QUICK DISCONNECTS

The Omniswivel 360 degree swivels and 90 degree elbows allows free range of motion & better low pressure hose routing. The Quick Disconnect allows a user to quickly disconnect a hose from their FFM. All items fit the Guardian Full Face Mask / Spectrum Full Face Mask & all standard 2nd stage regulators.





NOW WE'RE TALKING

OTS manufactures the best quality wireless underwater communications on the market and we've been doing so since 1984. Our state-of-the-art technology provides clarity and power that are second to none and are offered in all levels of our products ranging from entry to professional.





SPORT / RECREATIONAL

BUDDY PHONE D2 2-Channel Wireless Diver Unit

Using state-of-the-art technology, the Buddy Phone® D2 is the perfect wireless communications in a compact, affordable platform. It includes .5 watts of power and a voice menu via it's push-to-talk button to control channel, volume, squelch, and a patented studio quality microphone.



RX-100

1-Channel Receive Only Unit

The RX-100 Buddy Phone® Receive Only unit is a wireless listening device that easily mounts to all dive masks allowing for any diver to hear communications underwater. Eliminating the need to transmit, this product is perfect for instruction, classes, or guided tours.

SP-100D2

2-Channel Wireless Surface Station

The SP-100D2 is a compact lightweight battery operated two channel surface station easy to operate from a boat or shore. It includes a handheld microphone and transducer and its' .5 watt of power can communicate with all wireless products on the same channel and within range.



PUBLIC SAFETY / PROFESSIONAL

SSB-2010

4-Channel Wireless Diver Unit

A step up in power is the SSB-2010, harnessing 5 watts of power and designed with professional Search & Rescue teams in mind. Standard features include: voice-operated transmit, push-to-talk, squelch control, earphone volume, voice menu (allowing “on the fly” adjustments of the SSB-2010 underwater), removable transducer, and a heavy-duty design.



CDK-6

Surface Conversion Kit

The CDK-6 Surface Accessory Kit converts a SSB-2010 or SSB-1001B into a portable surface station. After a quick and easy installation, you can talk to divers within range and on the same channel. The Kit contains a deluxe headset w/boom microphone (THB-13) and a 55' transducer cable (TC-35S).

*Pictured with SSB-2010 (not included)

STX-101

4-Channel Surface Station

The Aquacom® STX-101 surface transceiver is a 5 watt, multi-channel, wireless surface station designed with the professional Search & Rescue teams in mind. The STX-101 offers four channels that match the SSB-2010 and includes a handheld microphone and transducer.



BELL UNITS / SPECIAL APPLICATIONS

BELL-200

Diving Bell Unit



Primarily used in diving bells or confined spaces, the Bell-200 is designed to meet the rugged demands of commercial, scientific, and military diving. Although compact in design, the Bell-200 packs a punch. It puts out 70 watts and is set to a standard frequency of 25 kHz. Other channels are available.

STX-101SB

Diving Bell Surface Unit

The Aquacom® STX-101SB is a high power surface transceiver designed to operate with the BELL 200 back-up communications system. Using a heavy-duty 35' transducer cable and transducer, the STX-101SB has 70 watts of power to ensure clear communications in virtually any condition. Includes handheld microphone.



STX-101SBR

Diving Bell Surface Unit



Front



Back side shown

The Aquacom® STX-101SBR is a high power, two-channel, rack mounted version of the STX-101SB designed to operate with the BELL 200 back-up communications system. It includes a heavy-duty 35' transducer cable with 70 watts of power, ensuring clear communications with the STX-101SBR.



DON'T MISS OUT!

Wireless underwater communications are a fun and easy way to freely stay connected underwater and ensure you never have to surface saying, "I can't believe I missed that!". You'll save time trying to navigate issues underwater by reducing the need for confusing hand signals, writing on slates, and the old fashioned bang on your tank method to grab your buddy's attention.



Wireless Comparison Chart



Buddy Phone D2 Diver Unit



RX-100-D2 Diver Unit



SP-100D-2 Surface Station



Aquacom SSB-2010 Diver Unit

Channels / Frequencies	Ch.1 32.768 kHz SB Ch.4 31.250 kHz LSB	Ch.1 32.768 kHz SB OR Ch.4 31.250 kHz LSB	Ch.1 32.768 kHz SB Ch.4 31.250 kHz LSB	Ch 1: 32.768 kHz SB Ch 2: 32.768 kHz LSB Ch 3: 31.250 kHz SB Ch 4: 31.250 kHz LSB
Output Power	0.5 Watts PEP	N/A	0.5 Watts PEP	5 watts PEP
Range*	50m 500m	Dependent on Transceiver sed	50m 500m	200m 1000m
Transducer	Piezoelectric	Piezoelectric	Piezoelectric	Piezoelectric
Transmit Control	Push To Talk, Optional Continuous Transmit	N/A	Manual Activation (Push To Talk)	Voice Operated Transmit (VOX) and Manual Activation (Push To Talk)
Microphone / Speakers / Earphone	Microphone / Earphone assembly integrated unit	Earphone assembly integrated unit	Handheld Mic (included), THB 14 Headset w/ boom mic (optional)	Ear / Mic Assembly via Hi se Connector (Purchased Separately)
Rec Out / Auxillary Speaker	No / No	No / No	Yes / No	No / No
Battery Type (Batteries Not Included)	Alkaline 9 Volt (type 522) or Lithium 9 Volt Cell	Alkaline 9 Volt (type 522) or Lithium 9 Volt Cell	16 AA Batteries	8 AA Batteries or RB 11 NiMH Rechargeable Battery Pack
Battery Life	~ 4.5 Hours	~ 5 Hours	~ 20 Hours	8 AA Batteries : ~ 7 hours RB 11 NiMH Battery Pack : ~ 12 hours
Low Battery Indicator	Voice Alert	Tone Alert	Tone Alert	Tone Alert / Flashing LED
External Power	N/A	N/A	12 VDC, Minimum of 1 Amp. Access via Mini Double Banana Plug on Front Panel	N/A
Depth Rating	130 FSW	130 FSW	35 FSW (Transducer)	300 FSW
Housing	Injection Molded, High Impact, Glass Filled ABS Plastic	Injection Molded, High Impact, Glass Filled ABS Plastic	nderwater inetics 309, ABS, Heavy Duty	Injection Molded, High Impact, Glass Filled ABS Plastic
Dimensions (H x W x D) / Weight	Height : 5.18", Width : 3.5" Depth : 2.0", Weight : 8.1 oz	Height : 5.18", Width : 3.5" Depth : 2.0", Weight : 8.1 oz	Height: 7.85", Width: 9.0", Depth: 3.7" Weight: 2.5 lbs	Height: 8.125", Width: 4.5", Depth: 2.25" Weight : 3.5 lbs

*Range can be more or less than stated and is dependent on water conditions (i.e., depth, noise, thermoclines, etc.). A combination of high sea state and acoustic shadowing will severely limit range.



ALL Ocean Technology Systems' communications are fully guaranteed against defects in materials and workmanship for a period of 1 year from the time of purchase. Our obligation under this warranty is limited to the replacement of any part or parts which prove to our satisfaction to have been defective, and which have not been misused or carelessly handled. Labor is guaranteed for 1 year from time of purchase.



**CDK-6
Conversion Kit****



**STX-101
Surface Station**



**Bell-200
Surface Station**



**STX-101SB
Surface Station**



**STX-101SBR
Surface Station**

Dependent on Diver Unit. Compatible with SSB 2010 / SSB 1001B	Ch 1: 32.768 kHz SB Ch 2: 32.768 kHz LSB Ch 3: 31.250 kHz SB Ch 4: 31.250 kHz LSB	25 kHz SB (Standard), Contact OTS for Additional Frequencies	8.0875 kHz SB OR 25 kHz SB	8.0875 kHz SB / 11kHz LSB OR 25 kHz SB / 32.768 SB
N/A	5 Watts PEP	70 Watts PEP	70 Watts PEP	70 Watts PEP
Dependent on Transceiver used	200m - 1000m	200 m to 6000 m	200m - 6000m (up to 10km w/ 8 kHz Transducer)	200m - 6000m (up to 10km w/ 8 kHz Transducer)
Piezoelectric	Piezoelectric	Piezoelectric	Piezoelectric	Piezoelectric
Voice Operated Transmit (VOX) and Manual Activation (Push To Talk)	Manual Activation (Push To Talk)	Manual Activation (Push To Talk)	Manual Activation (Push To Talk)	Manual Activation (Push To Talk)
THB 13 Headset w/ boom mic via Hi-se Connector	Handheld Mic (included), THB 101 Headset w/ boom mic (optional)	Optional THB BELL Headset w/ boom mic via MIL Spec Connector	Handheld Mic (included), THB 101 Headset w/ boom mic (optional)	Handheld Mic (included), THB STX 101SBR Headset w/ boom mic (optional)
Yes / No	Yes / Yes	No / No	Yes / No	No / No
8 AA Batteries or RB 11 NiMH Rechargeable Battery Pack	2 Alkaline 6 volt Batteries or 2 Rechargeable RB 6V Gel Cell batteries	External 24V @ 10 Amps Power, minimum	Supplied with 2 RB 6V Re chargeable Gel Cells. Do not use Alkaline Batteries.	N/A
8 AA Batteries : ~ 7 hours RB 11 NiMH Battery Pack : ~ 12 hours	Alkaline 6 Volt Batteries : ~20 hours Rechargeable RB 6V Gel Cell batteries : ~12 hours	N/A	~ 6 Hours	N/A
Tone Alert / Flashing LED	Tone Alert	Tone Alert / Flashing LED	Tone Alert / Flashing LED	N/A
N/A	12 VDC, Minimum of 1 Amp. Access via Mini Double Banana Plug on Front Panel	N/A	12 VDC, Minimum of 4 Amps .Access via Mini Double Banana Plug on Front Panel	24 VDC, Minimum of 10 Amps
55 FSW (Transducer)	35 FSW (Transducer)	Transducer : 2000 FSW Bell Unit : N/A (Dry Environments only)	100 FSW (Transducer)	N/A
Injection Molded, High Impact, Glass Filled ABS Plastic	Injection Molded, High Impact, Glass Filled ABS Plastic	Sealed NEMA Enclosure	Injection Molded, High Impact, Glass Filled ABS Plastic	Aluminum Rack Chassis
Height: 8.5", Width: 6.12", Depth: 4.00" Weight : 2.5 lbs	Height: 6.50", Width: 14.00", Depth: 10.60" Weight: 12 lbs	Height : 4.75", Width : 10.25", Depth : 4.40", Weight : 7 lbs	Height: 6.50", Width: 14.0", Depth: 10.60" Weight: 12 lbs	Height: 3.50", Width: 19.0", Depth: 8.00" Weight : 12 lbs

**Diver unit not included.



RELIABILITY WHEN IT COUNTS

Professionals around the world choose OTS for their underwater communication needs. We understand the importance of communications in the field, which is why quality, durability and reliability are the forefront of our design.



THE ALL NEW MK-III 3 DIVER BOX

The MK-III offers unprecedented performance at an affordable price! Designed for Commercial, Military and Professional divers, the MK-III has the ability to communicate with 3 divers simultaneously in loud, hard working conditions due to it's powerful speaker. The panel displays a 3 diver color coded section to allow a surface tender to quickly identify and adjust volumes on the fly. The connector panels have the ability to be switched as needed, quickly and easily.

UNLIKE ANY OTHER

Made for the most demanding environments and conditions, the MK-III 3 Diver Box offers features such as a modular connector panel and the ability to connect two boxes together for even more versatility. At an aggressive price point and loaded with features, the MK-III 3 Diver Box delivers an impressive package. When loud, intelligible hardwire communications is needed, don't compromise with any other box.



MODULAR CONECTOR PANEL

A modular connector panel makes swapping topside connectors for different CommRope connectors a breeze. Options include : MS, AMP, and Banana connectors.



CONNECT 2 BOXES TOGETHER

The ability to connect two boxes together gives even greater versaility to the MK-III 3 Diver Box by allowing up to 6 divers to talk simulatenously with a surface tender.



POWERFUL SPEAKER

The MK-III 3 Diver Box delivers incredible sound delivered by a powerful panel speaker, perfect for noisy environments where extreme volume is needed.



AUX. INPUT FOR MUSIC & PRE-RECORDED MESSAGES

A panel mounted AUX input makes playing music or pre-recorded messages easy with a simple RCA connector.



ACCESSORY COMPARTMENT LID

The easy to remove lid of the MK-III doubles as an accessory storage compartment for headsets, extra batteries and other accessories.



HARDWARE COMMUNICATIONS

COMMUNICATION ROPES

Available in 2 Colors



CR-4 Comm Rope is 100% Polyester, 7/16" static kern mantle rope designed with four specially configured wires down the center. We offer the CR-4 by the foot but also sell it complete with the connectors that suits your needs on either end. Available in standard non-floating or floating configurations and in 2 colors : (Blue / Yellow)

Comm Rope Bags that hold up to 200' are available for an additional purchase

COMBOX

1-Diver Station

A compact, self-contained one diver surface station, the ComBox allows clear 2-wire communications using a powerful 20-watt amplifier. With a rugged PTT control and "Silver Bullet" front speaker, the ComBox will deliver years of reliable service.



MK2-DCI

2-Diver Station

The versatile MK2-DCI provides one or two divers with clear communications in either 2-wire or 4-wire mode. In 4-wire mode, up to 6 divers can be 'stacked' to communicate with each other.



MK-7 BUDDYLINE

2-Diver Station

The MK-7 BuddyLine is a compact, self-contained surface station that gives clear communications in the 4-wire mode (round robin). The MK-7 was specifically designed for Search & Rescue teams to have an underwater communication device that required minimal set-up time. Newly updated way to connect battery reducing chance of a failure.



MK-III

3-Diver Station



The MK-IV Three-Diver surface station is designed to support military diving profiles. It allows two divers and a standby diver to communicate via hardwire communications in addition to the surface tender. An auxiliary connector for use with HeO₂ (Helium) de-scramblers is also included.

Hardwire Comparison Chart



ComBox Silver Bullet Surface Station



MK-2 DCI Surface Station



MK-7 Buddy Line Surface Station



MK-III Surface Station

Mode	2 Wire Only	2 Wire or 4 Wire	4 Wire Only	2 Wire or 4 Wire Only
Number of Divers	1	1 - 6	1 - 2 Can accommodate up to 4 with Y-Splitters	1 - 3
Transmit Control	Manual Activation (Push-To-Talk)	Topside : Push-To-Talk Diver : Hands-Free (4 Wire)	Topside : Hands-Free Diver : Hands-Free	Topside : Push-To-Talk Diver : Hands-Free (4 Wire)
Microphone / Speakers / Earphone	Microphone / Speaker Integrated Unit	Microphone / Speaker Integrated Unit	THB-7A Headset with Boom Mic Included	Microphone / Speaker Integrated Unit Headset sold separately
Rec Out / Auxiliary Speaker	Yes / Yes	Yes / Yes	Yes / No	Yes / Yes
Battery Type (Batteries Not Included)	8 or 16 AA Alkaline Batteries or RB-11 NiMH Rechargeable Battery Packs	2 Alkaline 6-volt Batteries or 2 Rechargeable RB-6V Gel-Cell batteries	8 AA Alkaline Batteries	12V, 7.2Ah, Lead-Acid Rechargeable Battery
Battery Life	~10 Hours	~20 Hours	~ 12 Hours	~12 Hours
Low Battery Indicator	N/A	Green / Yellow / Red LED Indicator with Tone Alert	N/A	Green / Yellow / Red LED Indicator with Tone Alert
External Power Source	12 VDC, Minimum of 3 Amps. Access via Mini Double Banana Plug on Front Panel	12 VDC, Minimum of 1 Amp. Access via Mini Double Banana Plug on Front Panel	N/A	12 VDC, Minimum of 3 Amps or 90-240 V AC, 50-60Hz
Housing	ABS, Heavy Duty	Ultra-High Impact ABS	Injection-Molded, High-Impact, Glass-Filled ABS Plastic	ABS, Heavy Duty
Dimensions (H x W x D) / Weight	Height: 7.85", Width: 9.00", Depth: 3.70" Weight: 3.5 lbs	Height: 6.5", Width: 14.0", Depth: 10.60" Weight: 14.0 lbs	Height: 6.72", Width: 4.35", Depth: 3.0" Weight: 1.5 lbs	Height: 10.75", Width: 16.75", Depth: 8.75" Weight: 19.5 lbs
Additional Features	Record Out	Record Out	Aux. Output	Modular Connector Panel, Ability to connect 2 boxes for up to 6 divers, Aux. input for music, Accessory Storage Lid



OUTFITTING THOSE WHO RISK THEIR LIVES

Since the inception of our company, OTS has long been the choice of militaries around the world. OTS is the only U.S. approved wireless communications manufacturer for purchase and use by the U.S. Navy. We continue to be one of the select choices for communication, full face mask training and innovative communication needs.



10 WATT UNITS

SSB-1001B1 8-CHANNEL DIVER UNIT

The Aquacom® SSB-1001B1 transceiver is a high power, 10 watt, 8-channel single sideband underwater communications unit configurable to operate with virtually any style full-face mask (FFM). With the addition of a CDK-6 Surface Accessory Kit, it is easily converted into a portable surface station.



STX-101M 8-CHANNEL SURFACE STATION

The Aquacom® STX-101M transceiver is a 10 watt, 8-channel wireless surface station designed to meet the demanding profile of the military diver. It operates with virtually all OTS Aquacom® and Buddy Phone® transceivers. Includes handheld microphone and transducer.



70 WATT UNITS

SW-1000-SC 2-CHANNEL DIVER UNIT

The Magnacom® SW-1000-SC is the most advanced, state-of-the-art underwater communication unit to date. A powerful 70-watt transmitter and diver-to-diver hardwire connection ensures long-range communications via wireless mode and secure communications via hardwire. An optional "Buddy Line" allows multiple divers to participate on the secure line. This item is sold to U.S. Military Personnel ONLY.



MAG-1003D 2-CHANNEL DIVER UNIT

A wireless unit only, the Magnacom® MAG-1003D is a variation of our Magnacom® SW-1000-SC, but without secure communications. It is a 70-watt, two-channel unit and comes standard with rechargeable NiMH batteries and a charger.



MAG-1004HS **2-CHANNEL DIVER UNIT**

The Magnacom® MAG-1004HS is a variant of the SW-1000-SC created for Homeland Security applications with different frequencies and without a “sleep mode.” A powerful 70 watt transmitter ensures long-range wireless communications and a diver-to-diver hardwire connection provides secure communications.



MAG-1004-TAC **2-CHANNEL DIVER UNIT**

The Magnacom® MAG-1004-TAC is a variant of the Magnacom® MAG-1004HS using a shorter (approx 4' cable) and locking connectors. The powerful 70-watt transmitter ensures long range communications. The Secure Mode allows the users a secure way to communicate.



MAG-1001S **2-CHANNEL SURFACE STATION**

The Magnacom® MAG-1001S surface station is a 70 watt, dual-channel single sideband surface station designed to meet the demanding needs of the military. The Magnacom MAG-1001S has many useful features and comes standard with battery, battery charger, and transducer.



MAG-1003PS **PORTABLE SURFACE STATION**

A through-water unit only, the Magnacom® MAG-1003PS is a variation of our Magnacom MAG-1003D designed to be a portable wireless surface unit. It features dual channels and comes standard with rechargeable NiMH batteries and a charger.



Military Comparison Chart



**SSB-1001B1
Diver Unit**



**STX-101M
Surface Station**



**SW-1000-SC
Diver Unit**



**MAG-1003D
Diver Unit**

Channels / Frequencies	Ch.1 : 32.768 kHz USB Ch.2 : 32.768 kHz LSB Ch.3 : 31.250 kHz USB Ch.4 : 31.250 kHz LSB Ch.5 : 28.500 kHz USB Ch.6 : 28.500 kHz LSB Ch.7 : 25.000 kHz USB Ch.8 : 25.000 kHz LSB	Ch.1 : 32.768 kHz USB Ch.2 : 32.768 kHz LSB Ch.3 : 31.250 kHz USB Ch.4 : 31.250 kHz LSB Ch.5 : 28.500 kHz USB Ch.6 : 28.500 kHz LSB Ch.7 : 25.000 kHz USB Ch.8 : 25.000 kHz LSB	Ch.A : 25.000 kHz USB Ch.B : F2 (Special)	Ch. A: 28.500 kHz LSB Ch. B: 32.768 kHz USB
Output Power	10 Watts PEP	10 Watts PEP	70 Watts PEP	70 Watts PEP
Range*	200m - 3000m	200m - 3000m	1000m - 6000m	1000m - 6000m
Transducer	Piezoelectric	Piezoelectric	Piezoelectric	Piezoelectric
Transmit Control	Voice-Operated Transmit (VOX) and Manual Activation (Push-To-Talk)	Manual Activation (Push-To-Talk)	Voice-Operated Transmit (VOX) and Manual Activation (Push-To-Talk)	Voice-Operated Transmit (VOX) and Manual Activation (Push-To-Talk)
Microphone / Speakers / Earphone	Ear / Mic Assembly via Hi-Use Connector (Purchased Separately)	Handheld Mic (included), THB-101 Headset w/ boom mic (optional)	Ear / Mic Assembly via Hi-Use Connector (Purchased Separately)	Ear / Mic Assembly via Hi-Use Connector (Purchased Separately)
Rec Out / Auxiliary Speaker	No / No	Yes / No	No / No	No / No
Battery Type (Batteries Not Included)	8 AA Batteries or RB-11 NiMH Rechargeable Battery Pack	2 Alkaline 6-volt Batteries or 2 Rechargeable RB-6V Gel-Cell batteries	RB-14 NiMH Battery Pack (Included)	RB-14 NiMH Battery Pack (Included)
Battery Life	8 AA Batteries : ~ 7 hours RB-11 NiMH Battery Pack : ~ 8 hours	Alkaline 6-Volt Batteries : ~20 hours Rechargeable RB-6V Gel-Cell batteries : ~12 hours	~ 4 Hours on High-Power (Ch. A) ~ 8 Hours on Low-Power (Ch. B)	~ 4 Hours on High-Power (Ch. A) ~ 8 Hours on Low-Power (Ch. B)
Low Battery Indicator	Tone Alert / Flashing LED	Tone Alert	Tone Alert / Flashing LED	Tone Alert / Flashing LED
External Power	N/A	12 VDC, Minimum of 1 Amp. Access via Mini Double Banana Plug on Front Panel	N/A	N/A
Depth Rating	300 FSW	55 FSW (Transducer)	300 FSW	300 FSW
Housing	Injection-Molded, High-Impact, Glass-Filled ABS Plastic	Injection-Molded, High-Impact, Glass-Filled ABS Plastic	Injection-Molded, High-Impact, Glass-Filled ABS Plastic	Injection-Molded, High-Impact, Glass-Filled ABS Plastic
Dimensions (H x W x D) / Weight	Height : 8.1", Width : 4.5" Depth : 2.25", Weight : 3.5 lbs	Height: 6.50", Width: 14.00", Depth: 10.60" Weight: 12 lbs	Height: 8.25", Width: 4.50", Depth: 2.25" Weight: 5.5 lbs	Height: 8.25", Width: 4.50", Depth: 2.25" Weight: 5.5 lbs

*Range can be more or less than stated and is dependent on water conditions (i.e., depth, noise, thermoclines, etc.). A combination of high sea state and acoustic shadowing will severely limit range.



**MAG-1004HS
Diver Unit**



**MAG-1004-TAC
Diver Unit**



**MAG-1001S
Surface Station**



**MAG-1003PS
Surface Station**

Ch. A: 28.500 kHz LSB Ch. B: 32.768 kHz USB	Ch. A: 28.500 kHz LSB Ch. B: 32.768 kHz USB	Low-frequency / High Frequency Pair: Ch. A: 8.0875 kHz USB / 28.500 kHz LSB Ch. B: 11.0000 kHz LSB / 32.768 kHz USB	Ch. A: 28.500 kHz LSB Ch. B: 32.768 kHz USB
70 Watts PEP	70 Watts PEP	70 Watts PEP	70 Watts PEP
1000m - 6000m	1000m - 6000m	1000m - 6000m	1000m - 6000m
Piezoelectric	Piezoelectric	Piezoelectric	Piezoelectric
Voice-Operated Transmit (VOX) and Manual Activation (Push-To-Talk)	Voice-Operated Transmit (VOX) and Manual Activation (Push-To-Talk)	Manual Activation (Push-To-Talk)	Voice-Operated Transmit (VOX) and Manual Activation (Push-To-Talk)
Ear / Mic Assembly via Hi- Use Connector (Purchased Separately)	Ear / Mic Assembly via Hi- Use Connector (Purchased Separately)	Handheld Mic (included), THB-MAG Headset w/ boom mic (optional)	THB-13 Headset w/ boom mic (Included)
No / No	No / No	Yes / No	No / No
RB-14 NiMH Battery Pack (Included)	RB-14 NiMH Battery Pack (Included)	2 Rechargeable RB-6V Gel-Cell batteries	RB-14 NiMH Battery Pack (Included)
~ 4 Hours on High-Power (Ch. A) ~ 8 Hours on Low-Power (Ch. B)	~ 4 Hours on High-Power (Ch. A) ~ 8 Hours on Low-Power (Ch. B)	Rechargeable RB-6V Gel- Cell batteries : ~8 hours	~ 4 Hours on High-Power (Ch. A) ~ 8 Hours on Low-Power (Ch. B)
Tone Alert / Flashing LED	Tone Alert / Flashing LED	Tone Alert	Tone Alert / Flashing LED
N/A	N/A	N/A	N/A
300 FSW	300 FSW	55 FSW (Transducer)	35 FSW
Injection-Molded, High- Impact, Glass-Filled ABS Plastic	Injection-Molded, High- Impact, Glass-Filled ABS Plastic	Injection-Molded, Ultra High-Impact, Glass-Filled ABS Plastic	Injection-Molded, High- Impact, Glass-Filled ABS Plastic
Height: 8.25", Width: 4.50", Depth: 2.25" Weight: 5.5 lbs	Height: 8.25", Width: 4.50", Depth: 2.25" Weight: 5.5 lbs	Height : 6.50", Width : 14.0", Depth : 10.60", Weight : 12 lbs	Height: 8.25", Width: 4.50", Depth: 2.25" Weight: 6.5 lbs



ALL Ocean Technology Systems' communications are fully guaranteed against defects in materials and workmanship for a period of 1 year from the time of purchase. Our obligation under this warranty is limited to the replacement of any part or parts which prove to our satisfaction to have been defective, and which have not been misused or carelessly handled. Labor is guaranteed for 1 year from time of purchase.



CROWLEY

SCOUT

PDR-100
PORTABLE
DIVER
RECALL



MANUFACTURED BY
OCEAN TECHNOLOGY SYSTEMS
U.S.A.

LEAVE NO ONE BEHIND

OTS Diver Recall Systems are known for their durability and reliability ensuring mass communication is made when it's needed. OTS offers Diver Recall options for divers to be recalled by either tone or voice. When you need fast and simple broadcasting to the masses we have the solution for you.



DIVER RECALL SYSTEMS

DRS-100B

Diver Recall System

The DRS-100B alerts divers within range with either voice, a solid tone, or an intermittent tone. You can also feed sound into the water (e.g. music, pre-recorded announcements) via a line-in connection located on the front panel. The DRS-100B also has a listen mode allowing the user to listen to marine and/or man-made noise.



PDR-100

Portable Diver Recall

The PDR-100 was designed with Military, Public Safety and Commercial applications in mind. Designed with a rugged housing and durable underwater speaker, this compact Portable Diver Recall system is made for a long working life under harsh environments.



SCB-1

8 Cell AA Battery Holder

The SCB-1 was designed to give users the option to use AA batteries in the PDR-100. This is an essential item for days where longer battery life is required.



Diver Recall Comparison Chart



PDR-100
Portable Diver Recall



DRS-100B
Diver Recall System

Tone / Siren Recall	Yes / Yes	Yes / Yes
Output Power	15 Watts	Recall & Tone : 132 Watts Voice : Adjustable up to 132 Watts
Range*	300m	Voice : 100m Tone : 300m
Transducer	PVC housing with Epoxy Coated Piezo Elements	Anodized Aluminium
Transmit Control	Tone / Siren : Toggle Switch	Tone / Recall : Toggle Switch Voice : Push-To-Talk Handheld Microphone
Battery Type (Batteries Not Included)	RB-14, NiMH 12, 2Ah	2 12V, 6Ah Rechargeable Batteries
Rec Out / Auxiliary Speaker	No / No	Yes / No
Battery Life	~5 Hours (20% Duty) ~36 Hours Standby	~5 Hours (20% Duty) ~3 Hours Aux Input (Continuous)
Low Battery Indicator	Multicolor LED	Red Flashing LED
External Power Source	N/A	24 VDC; 7 Amps Maximum; 75mA (Idle)
Speaker / Transducer Depth Rating	30 FSW	25 FSW
Housing	Injection-Molded, High-Impact, Glass-Filled ABS Plastic	Ultra-High Impact ABS
Dimensions (H x W x D) / Weight	Height: 7.0", Width: 4.50", Depth: 2.25" Weight: 7.5 lbs	Height: 6.5", Width: 14.0", Depth: 10.0" Weight: 15 lbs

*Range can be more or less than stated and is dependent on water conditions (i.e., depth, noise, thermoclines, etc.). A combination of high sea state and acoustic shadowing will severely limit range.



ALL Ocean Technology Systems' communications are fully guaranteed against defects in materials and workmanship for a period of 1 year from the time of purchase. Our obligation under this warranty is limited to the replacement of any part or parts which prove to our satisfaction to have been defective, and which have not been misused or carelessly handled. Labor is guaranteed for 1 year from time of purchase.




AUDIO RECORDING



Photo by : Trent Ellis --- Cinematographer : David Reichert

CAPTURE EVERY MOMENT

Our Emmy Award Winning Technology has revolutionized the way underwater story telling is told for Film & Television. As pioneers and experts in recording underwater audio to cameras, we offer the best quality and clarity in the field satisfying any film or television production need.





RX-100-D-RO

Receive Only with Audio out
Patch Cable

The RX-100-D-RO Buddy Phone® Receive Only unit is designed to plug into a Female E/O connector on your camera housing and feed live audio into the microphone input on your camera. The RX-100-D-RO is an excellent choice if you are seeking to record all wireless transmissions into the camera.



VSB-2

Audio Splitter Cable

The VSB-2 Audio Adaptor allows the SSB-2010 or 1001B to connect to an underwater video housing. This is the perfect option for camera operators who need their own audio directly piped into the camera as well as receiving all other wireless transmissions. Includes female bulkhead connector.

RECORDER HOUSING

Underwater Recorder Housing

This underwater recorder housing is a perfect system for those looking for a complete standalone option for recording audio. Pair this with a RX-100-D-RO and you have full system to record underwater audio.



COMMUNICATION ROPES

Direct Audio Recording

Comm Ropes offer the cleanest form of audio recording available. When the best possible sounding audio is necessary, pairing a communication rope to a diver with a surface station is the best way to go.

EXPERT SERVICES FOR FILM & TELEVISION

OTS offers a vast array of underwater services to ensure your production needs are met. We specialize in :

- Training talent to look and sound their best.
- Creative audio solutions.
- Audio to camera set-up consultation.
- Specials and props.
- Expert advising for film.
- Hardwire and Wireless systems available for rent or sale.

FILM & TELEVISION PROJECTS

A few projects OTS has been a part of :

Titanic, Sphere, Shark Week, Italian Job, Into the Blue, The Meg, Bering Sea Gold, Piranha 3D, Sanctum, Pirates of the Caribbean, Full House, The Travel Channel, Animal Planet, 60 Minutes, Jaws 4, Pearl Harbor, The Hulk

WINNING THE EMMY!

In 1991, Michael, Jerry, and OTS were presented with a National Emmy Award for the impact underwater communications had on film making. The use of underwater communications allowed for talents to talk real time on camera and for film makers to seamlessly direct underwater. The Emmy award winning documentary, "Expedition Earth," starring Peter Benchly and Stan Waterman, was filmed at Cocos Island with underwater shooter Marty Snyderman and underwater sound shooter Michael Pelissier.



Today, OTS has made a name for itself in the television and film industry. It is not uncommon to turn on the television and see someone using an OTS Guardian Full Face Mask or Spectrum Full Face Mask and OTS underwater communications.





Planet Scuba India Pvt Ltd

No.1315, Double Road, 2nd Stage Indiranagar, Bangalore - 560 038.

Tel : +91-9686466833, +91-9901700500, + 91-80-41573939

E-mail : sales@planetscubaindia.com | www.planetscubaindia.com

Copyright © 2019 Undersea Systems International, Inc. dba Ocean Technology Systems

All rights reserved • Specifications subject to change without prior notice • Printed in USA • Part Number 507014-019 (Rev. A)

Front Cover Photo : Janice Carter, Scuba Chick Photography – Back Cover Photo : Dive SAGA