



Planet Scuba India Pvt Ltd

1315, Double Rd, Eshwara Layout,
Indiranagar, Bengaluru - 560038

Tel: +91-80-41573939,

+91-8431242337, +91-8660241715

Email: sales@planetscubaindia.com

Website: www.planetscubaindia.com



Data Sheet

DHC-2 HD Diver Held Camera



- *** NEW * 1080p HD-TVI video**
- *** NEW * 0.01 lux low light, 1080p color camera**
- **Compact camera & lighting system**
- **1,000 foot depth rating - optional**
- **Surface powered for extended operations**
- **Adjustable, 3000 lumen LED lighting**
- **Carrying case for camera - optional**

System Information

- Camera - .01 lux, 1920 x 1080p, 2.1 mega-pixel camera
- Light - Two, adjustable 1500 lumen LED lights
- Operating depth - 1,000 feet
- Sealing - O-ring sealed; Contains leak detector
- Power Requirements - 100 to 240 vac

Dimensions and Weights

- Camera housing - 11"L x 4.5" diameter - 7 lbs. (air); 6 oz. (water)
- Cable - .4"D x 150' to 1,000' - 20 to 135 lbs. (air); 4-30 lbs. (water)
- LED light and camera control box - 14" x 10" x 6" - 9 lbs.

The new JW Fishers DHC-2 HD Diver Held Camera system is the next generation video camera now coming standard with full-HD video! The HD-TVI camera produces 1920 x 1080 (1080p) full-HD video for sharp, detailed imaging. HD-TVI technology supports longer cable transmission distances while allowing the picture to still travel over standard coax cable, producing a zero-latency, high definition video experience. It is the ideal tool for hull inspections, bridge inspections, or any of the numerous underwater structure inspections encountered by today's commercial diver. The DHC-2 HD is ruggedly constructed of corrosion proof materials making it an excellent choice for work in depths of up to 1,000 feet. The system includes two powerful 1500 lumen LED lights with operation of the lights and camera controlled by the diver through a switch on the rear of the housing. The DHC-2 is surface powered allowing unlimited operating time for underwater operations.

The picture can be viewed on a video monitor, a TV with an HDMI output or Fishers VRM-2 HD.

The DHC-2 HD is protected by leak detection circuitry that informs both diver, and topside personnel. The included 150 foot cable has a highly abrasion resistant urethane jacket and waterproof connector.

Available Options:

- 1,000' depth rated housing
- Cable lengths up to 1,000 feet
- VRM-2 HD
- CMS Cable Management System
- Hard carry case

